

OpenGL 3 & 4

CSCI 4239/5239

Advanced Computer Graphics

Spring 2015

What is new in OpenGL 3&4

- Additional shaders
 - Geometry (OpenGL 3.2)
 - Tesselation (OpenGL 4.0)
 - Compute (OpenGL 4.3)
- New syntax for passing variables
 - “in” from previous stage
 - “out” to next stage
 - Deprecating most predefined variables
- Building objects from vertex arrays
- Deprecating OpenGL transformations

Deprecated Features

- `glBegin()` `glEnd()`
 - Use vertex buffer objects instead
- `glTranslate()` `glRotate()` `glScale()`
 - Use `vmath` or `glm` or roll your own
- Display lists
- *Deprecated features remain available through the compatibility profile, but are not available in the core profile which is common with OpenGL ES*

Vertex Arrays

- Pass all the vertex values to OpenGL as a single array of values rather than numerous calls to `glVertex`, `glColor`, etc.
- Draw objects using `glDrawArrays()` or `glDrawElements()`

Vertex Buffer Objects (VBO)

- Stored on the GPU
- Addressed analogous to textures
 - glGenBuffers() - generate unique names
 - glBindBuffer() - select buffer
 - glBufferData() - copy data to buffer
 - glBufferSubData() - copy partial data
 - glEnableVertexAttribArray() - enable array
 - glVertexAttribPointer() - map attribute

glVertexAttribPointer(index,size,type,normalized,stride,pointer)

- index: 0,1,.. must match layout
- size: dimension of variable (1,2,3,4)
- type: variable type (e.g. GL_FLOAT)
- normalize: if true map integers to 0-1
- stride: bytes between data values
- pointer: offset of data values (in bytes)
- *The data comes from the current vertex buffer selected using glBindBuffer()*
- Activate glEnableVertexAttribArray(index)